KA0805 Readme File

Principal Investigator/Organization:

Dr. Richard Feely NOAA/PMEL 7600 Sand Point Way NE Seattle, WA 98115 (206) 526-6214 Richard.A.Feely@noaa.gov

Ship Name: Ka'imimoana

Call Sign: WTEU
Country: United States

Ship Owner: National Oceanic and Atmospheric Administration (NOAA)

Temporal Coverage:

Cruise Start: August 6, 2008; Honolulu, Hawaii Cruise End: September 1, 2008; Kwajalein

Shoreside support/Data Reduction: Cathy Cosca, cathy.cosca@noaa.gov

System Operators: Tonya Watson (Survey Tech)

Dataset ID/Location: KA0805.csv (www.pmel.noaa.gov/co2/uwpco2/)

Experiment Name: Underway measurement of atmospheric and surface water pCO2

Geographical Bounds (+ E, - W for Longitude; + N, - S for Latitude):

Westernmost Longitude: 169.993 Easternmost Longitude: -154.806 Northernmost Latitude: 19.811 Southernmost Latitude: -8.282

Method Description:

Equilibrator type/specifications: Showerhead, volume of ~ 0.5 L with a headspace of ~ 0.8 L.

Water Flow rate: 3.5 L/minute

Headspace gas flow rate: 60 ml/minute

Measurement method: Infrared absorption of dried gas.

CO2 Sensor: Licor 6262, Serial # IRG3-1295

Resolution/Uncertainty: 0.3 uatm for equilibrator measurements, 0.2 utam for atmospheric

measurements.

The general principle of instrumental design and operation are described in:

Feely, R.A., R. Wanninkhof, H.B. Milburn, C.E. Cosca, M. Stapp, and P.P. Murphy, A new automated underway system for making high precision pCO2 measurements onboard research ships, Analytica Chim. Acta, 377, 185-191, 1998.

and

Wanninkhof and Thoning, Measurement of fugacity of Carbon Dioxide in surface water and air using continuous sampling methods, Marine Chemistry, 44, 189-205, 1993.

Standard gases:

Standard gases are supplied by NOAA's Climate Monitoring Diagnostics Laboratory in Boulder, CO, and are directly traceable to the WMO scale. Any value outside the range of the standards should be considered approximate, although the general trends should be indicative of the seawater chemistry.

Serial numbers and CO2 concentrations for the cylinders used on this cruise:

CA03065	364.08
CA06867	421.13
CC115011	466.38
CA07519	543.65

Sampling Cycle:

The system runs a full cycle in approximately 112 minutes. The cycle starts with 4 standard gases, then measures 10 atmospheric samples followed by 60 surface water samples. Each new gas is flushed through the Licor Analyzer for 4 minutes prior to a 10 second reading from the analyzer during which the sample cell is open to the atmosphere. Subsequent samples of the same gas are flushed through the Licor Analyzer for 30 seconds prior to a stop-flow measurement.

Units:

All xCO2 values are reported in parts per million by volume (ppmv) and fCO2 values are reported in microatmospheres (uatm) assuming 100 % humidity at the equilibrator temperature.

Calculations:

The mixing ratios of ambient air and equilibrated headspace air are calculated by fitting a second-order polynomial through the hourly averaged response of the detector versus mixing ratios of the standards. Mixing ratios of dried equilibrated headspace and air are converted to fugacity of CO2 in surface seawater and water saturated air in order to determine the fCO2. For ambient air and equilibrator headspace the fCO2a, or fCO2eq is calculated assuming 100% water vapor content:

fCO2a/eq = xCO2a/eq(P-pH2O)exp(B11+2d12)P/RT

where fCO2a/eq is the fugacity in ambient air or equilibrator, pH2O is the water vapor pressure at the sea surface temperature, P is the atmospheric pressure (in atm), T is the SST or equilibrator temperature (in K) and R is the ideal gas constant (82.057 cm^3·atm·deg^-1·mol^-1). The exponential term is the fugacity correction where B11 is the second virial coefficient of pure CO2

$$B11 = -1636.75 + 12.0408T - 0.032795T^2 + 3.16528E-5 T^3$$

and d12 = 57.7 - 0.118 T

is the correction for an air-CO2 mixture in units of cm³·mol⁻¹ (Weiss, 1974).

The calculation for the fugacity at SST involves a temperature correction term for the increase of fCO2 due to heating of the water from passing through the pump and through 5 cm ID PVC tubing within the ship. The water in the equilibrator is typically 0.2 °C warmer than sea surface temperature. The empirical temperature correction from equilibrator temperature to SST is outlined in Weiss et al. (1982).

$$dln(fCO2) = (teq-SST)(0.0317-2.7851E-4 teq - 1.839E-3 ln(fCO2eq))$$

where dln(fCO2) is the difference between the natural logarithm of the fugacity at teq and SST, and teq is the equilibrator temperature in degrees C.

File Format

	COLUMN HEADER	DESCRIPTION
1.	GROUP/SHIP:	PMEL/Ka'imimoana
2.	CRUISE_ID:	KA <year><nth cruise="" of="" year=""></nth></year>
3.	JD_GMT:	Decimal year day
4.	Date_DDMMYYYY	Date in the format DDMMYYYY
5.	TIME_HH:MM:SS:	GMT HH:MM:SS
6. are in	LAT_DEC_DEGREE:	Latitude in decimal degrees (negative values
		southern hemisphere).
7. are	LONG_DEC_DEGREE:	Longitude in decimal degrees (negative values
		in western latitudes).

8.	xCO2W_PPM:	in	Mole fraction of CO2 (dry) in the headspace equilibrator at equilibrator temperature (Teq) parts per million. Water comes from bow intake 2m below the water line.
9 millio	xCO2A_PPM: n.		Mole fraction of CO2 in air in parts per
10 with	xCO2A_INTERPOLATED_PPM:		xCO2atm_ppm averaged linearly to match up measurements xCO2eq_ppm
11	PRES_EQUIL_hPa:		Barometric pressure in the equilibrator
12	PRES_SEALEVEL_hPa:		Barometric pressure in the atmosphere
13.	EqTEMP_C:		Temperature in the equilibrator water.
14.	SST(TSG)_C:		Temperature from the ship's bow intake.
15.	SAL(TSG)_PERMIL:		Thermosalinograph salinity
16.	fCO2W@SST_uATM:		Fugacity of CO2 in sea water in microatmospheres calculated as outlined in the DOE Handbook.
17.	CO2A_uATM:		Fugacity of CO2 in air in microatmospheres
18. micro	dfCO2_uatm: atmospheres.		Sea water fCO2 - air fCO2 in
19.	QC_FLAG:		Quality control flag 2 = Good value 3 = Questionable value 4 = Bad value
20. value	QC_SUBFLAG:		Descriptive quality control flag used when a receives a "3" QC flag 1 = Outside of Standard Range 2 = Questionable/interpolated SST 3 = Questionable EQU temperature 4 = Anomalous ΔT (EqT – SST)(± 1°C) 5 = Questionable Sea Surface Salinity

6 = Questionable pressure

7 = Low EQU gas flow

8 = Questionable air value

9= Interpolated standard value

10 = Other, see metadata

References

- DOE (1994). Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. A.G. Dickson and C. Goyet, eds., ORNL/CDIAC-74
- Feely, R.A., R. Wanninkhof, H.B. Milburn, C.E. Cosca, M. Stapp, and P.P. Murphy, A new automated underway system for making high precision pCO₂ measurements onboard research ships, Analytica Chim. Acta, 377, 185-191, 1998.
- Wanninkhof, R. and K. Thoning (1993) Measurement of fugacity of CO₂ in surface water using continuous and discrete sampling methods. Mar. Chem. 44(2-4): 189-205.
- Weiss, R. F. (1970) The solubility of nitrogen, oxygen and argon in water and seawater. Deep-Sea Research 17: 721-735.
- Weiss, R. F. (1974) Carbon dioxide in water and seawater: the solubility of a non-ideal gas. Mar. Chem. 2: 203-215.
- Weiss, R. F., R. A. Jahnke and C. D. Keeling (1982) Seasonal effects of temperature and salinity on the partial pressure of CO₂ in seawater. Nature 300: 511-513.

For questions or comments contact: Cathy Cosca NOAA/PMEL 7600 Sand Point Way NE Seattle, WA 98115 206-526-6183 cathy.cosca@noaa.gov